

Water Supply

AVK offers a wide range of fixed and height adjustable surface boxes in various dimensions, which can be used in many fields of application. Apart from economic benefits, AVK synthetic surface boxes are lightweight, user-friendly, easy to open, noiseless and maintenance free. Most of AVK surface boxes are designed and approved according to DIN/EN standards, but can also be designed according to local standards or customer specifications. The carbon footprint (CO₂ emission) of synthetic surface boxes, measured from resource to end of life, is significantly lower compared to surface boxes made of traditional materials, making AVK surface boxes ecologically sound.

Use:

Fixed height surface box with cast iron lid and square top, for service connection valves, design derived from DIN 4057, standard lid inscription: AVK W

Features:

- Lightweight, user-friendly, silent and maintenance free
- 100% recyclable and significantly less use of resources compared to traditional materials
- Manufactured out of high grade recycled materials
- Ribs in housing ensure optimal fixation in road foundation
- Selected materials for housing and lid ensure easy opening at all times
- Heat resistant to max. 250 °C
- Suitable for low-temperature applications
- Locking clip around the bolt ensuring lid will stay in its place
- Due to square top ideal solution for pavement installation
- B125 load bearing capacity on complete surface*

Design:

- Design derived from DIN 4057

Optional

- Various colours and lid inscriptions possible
- Available as lockable version making the surface box tamperproof

*Results of the load-bearing capacity test on the complete surface, following the internally used load application method, and declaring the load-bearing capacity according to the corresponding class as per EN 124-1:2015, clause 7.2, table 4

Accessories:

Support tile UST


Top frame service connection



SYNTHETIC SURFACE BOX TYPE 4057

80/32-211

For service connection valves, M-4057P MD-GG, Futura



Component list:

1. Lid	Cast iron GJL-200 (GG-20)	3. Locking clip	PP
2. Housing	PA+	4. Bolt, hexagon head	Stainless steel A2-70

Metallic components may be substituted with equivalent or higher-grade materials without prior notice, provided that this is in compliance with the approvals.

Reference nos. and dimensions:

Reference no.	Do1 mm	DI mm	Dc1 mm	Di1 mm	Df mm	H3 mm	Weight Box / kg	Weight Lid / kg	Theoretical weight/kg
80-32-2110001	144	121	101 / 72	137	202	250	1.0	1.1	2.1
80-32-2110003	144	121	101 / 72	137	202	250	1.0	1.1	2.1
80-32-2110004	144	121	101 / 72	137	202	250	1.0	1.1	2.1