

Water Supply

Wastewater Treatment

Gas Supply

AVK offers a wide range of fixed and height adjustable surface boxes in various dimensions, which can be used in many fields of application. Apart from economic benefits, AVK synthetic surface boxes are lightweight, user-friendly, easy to open, noiseless and maintenance free. Most of AVK surface boxes are designed and approved according to DIN/EN standards, but can also be designed according to local standards or customer specifications. The carbon footprint (CO₂ emission) of synthetic surface boxes, measured from resource to end of life, is significantly lower compared to surface boxes made of traditional materials, making AVK surface boxes ecologically sound.

Use:

Fixed height surface box with synthetic lid, for service connection valves, standard inscription plate: WATER or GAS

Features:

- Lightweight, user-friendly, silent and maintenance free
- 100% recyclable and significantly less use of resources compared to traditional materials
- Manufactured out of high grade recycled materials
- Selected materials for housing and lid ensure easy opening at all times
- Heat resistant to max. 250 °C
- Suitable for low-temperature applications
- Limited installation depth required
- Click system ensuring lid will stay in place
- Galvanized steel cable connection between lid and surface box
- Lid material discourages thieves; no value in stealing
- Synthetic lid enables signal transmission
- Acceptance and fixation of down pipes Ø 75, 90, 98, 110 and 118mm directly in surface box
- B125 load bearing capacity on complete surface*

Optional

- Various colours and lid inscriptions possible

*Results of the load-bearing capacity test on the complete surface, following the internally used load application method, and declaring the load-bearing capacity according to the corresponding class as per EN 124-1:2015, clause 7.2, table 4

Accessories:


Support tile UST



SYNTHETIC SURFACE BOX MP

For service connection valves, Surface box MP LD-KU

80/22-025



Component list:

1.	Lid	PA+	3.	Cable	Steel, galvanized
2.	Housing	PA+	4.	Inscription plate	PA 6

Metallic components may be substituted with equivalent or higher-grade materials without prior notice, provided that this is in compliance with the approvals.

Reference nos. and dimensions:

Reference no.	Do1	DI	Dc1	Di1	Df	H3	Weight	Weight	Theoretical
	mm	mm	mm	mm	mm	mm	Box / kg	Lid / kg	weight/kg
80-22-0250000 (1)	121	96	80	130	193	157	0.6	0.1	0.7
80-22-0250010 (2)	121	96	80	130	193	157	0.6	0.1	0.7
(1) Inscription AVK W									
(2) Inscription plate: WATER (blue)									