

Fire Protection

AVK offers a wide range of fixed and height adjustable surface boxes in various dimensions, which can be used in many fields of application. Apart from economic benefits, AVK synthetic surface boxes are lightweight, user-friendly, easy to open, noiseless and maintenance free. Most of AVK surface boxes are designed and approved according to DIN/EN standards, but can also be designed according to local standards or customer specifications. The carbon footprint (CO₂ emission) of synthetic surface boxes, measured from resource to end of life, is significantly lower compared to surface boxes made of traditional materials, making AVK surface boxes ecologically sound.

Use:

Fixed height surface box with cast iron lid, for underground hydrants, standard lid inscription: HYDRANT

Features:

- Lightweight, user-friendly, silent and maintenance free
- 100% recyclable and significantly less use of resources compared to traditional materials
- Manufactured out of high grade recycled materials
- Ribs in housing ensure optimal fixation in road foundation
- Selected materials for housing and lid ensure easy opening at all times
- Heat resistant to max. 250 °C
- Suitable for low-temperature applications
- C250 load bearing capacity on complete surface*

Design/Test/Approval:

- Designed according to DIN 4055
- Tested according to DIN 3580-2
- DVGW certificate DW-6430BP0136

Optional

- Spring around bolt ensuring lid will stay in its place
- Various colours and lid inscriptions possible
- Available as lockable version making the surface box tamperproof
- Use of a Flexdrain around the hydrant prevents dirt to block the drain pipe, ensuring optimal operation

*Results of the load-bearing capacity test on the complete surface, following the internally used load application method, and declaring the load-bearing capacity according to the corresponding class as per EN 124-1:2015, clause 7.2, table 4


Accessories:

Support tile II
Support tile III



SYNTHETIC SURFACE BOX TYPE 4055
For underground hydrants, H-4055 HD-GG, Classic

80/30-000



Component list:

1.	Lid	Cast iron GJL-200 (GG-20)
2.	Housing	PA+
3.	Bolt, hexagon head	Stainless steel A2-70

Metallic components may be substituted with equivalent or higher-grade materials without prior notice, provided that this is in compliance with the approvals.

Reference nos. and dimensions:

Reference no.	Do1 mm	Dc1 mm	Di1 mm	Df mm	DI mm	Weight Box / kg	Weight Lid / kg	Theoretical weight/kg
80-30-0000000	376 / 268	274 / 207	340 / 236	420 / 316	345 / 240	4.0	10.8	14.8