

SYNTHETIC SURFACE BOX TYPE 4056

80/31-100

For distribution valves, H-4056V HD-GG, Classic

Water Supply

AVK offers a wide range of fixed and height adjustable surface boxes in various dimensions, which can be used in many fields of application. Apart from economic benefits, AVK synthetic surface boxes are lightweight, user-friendly, easy to open, noiseless and maintenance free. Most of AVK surface boxes are designed and approved according to DIN/EN standards, but can also be designed according to local standards or customer specifications. The carbon footprint (CO₂ emission) of synthetic surface boxes, measured from resource to end of life, is significantly lower compared to surface boxes made of traditional materials, making AVK surface boxes ecologically sound.

Use:
Height adjustable surface box with cast iron lid, for distribution valves, design according to DIN 4056, standard lid inscription: W

Features:

- Lightweight, user-friendly, silent and maintenance free
- 100% recyclable and significantly less use of resources compared to traditional materials
- Manufactured out of high grade recycled materials
- Ribs in housing ensure optimal fixation in road foundation
- Selected materials for housing and lid ensure easy opening at all times
- Heat resistant to max. 250 °C
- Suitable for low-temperature applications
- Large height range and flexible positioning of top part
- Inscription in lid to be positioned easily
- No height adjustment needed after installation, saving time and costs
- Floating top part following road settlement ensuring perfect alignment at all times
- O-ring only to be used for determining final position of top part
- D400 load bearing capacity on complete surface*

Design/Test/Approval:

- Designed according to DIN 4056
- Tested according to DIN 3580-2
- DVGW certificate DW-6430BP0142

Optional

- Available as lockable version making the surface box tamperproof
- Various colours and lid inscriptions possible
- Spring around bolt ensuring lid will stay in its place

*Results of the load-bearing capacity test on the complete surface, following the internally used load application method, and declaring the load-bearing capacity according to the corresponding class as per EN 124-1:2015, clause 7.2, table 4

Accessories:


Support tile UST



The designs, materials, dimensions and specifications shown are subject to change without notice due to the continuous development of our product range.

SYNTHETIC SURFACE BOX TYPE 4056
For distribution valves, H-4056V HD-GG, Classic

80/31-100



Component list:

1. Lid	Cast iron GJL-200 (GG-20)	4. O-ring	EPDM rubber
2. Housing top part	PA+	5. Housing bottom part	PA+
3. Bolt, socket head	Stainless steel A2-70		

Metallic components may be substituted with equivalent or higher-grade materials without prior notice, provided that this is in compliance with the approvals.

Reference nos. and dimensions:

Reference no.	Do1 mm	DI mm	Dc1 mm	Di1 mm	Di2 mm	Df mm	H3 mm	X mm	Weight Box / kg	Weight Lid / kg	Theoretical weight/kg
80-31-1000000 (1)	182	160	118 / 95	129	185	270	365-485	80-200	3.0	3.9	6.9
80-31-1000010 (2)	182	160	118 / 95	129	185	270	365-485	80-200	3.0	3.9	6.9
80-31-1000014 (3)	182	160	118 / 95	129	185	270	365-485	80-200	3.0	3.9	6.9
80-31-1000015 (4)	182	160	118 / 95	129	185	270	365-485	80-200	3.0	3.9	6.9

(1) Inscription: W
(2) Inscription EAU/WASSER/ACQUA
(3) Inscription: GAS
(4) Inscription AVK ACQUA

The designs, materials, dimensions and specifications shown are subject to change without notice due to the continuous development of our product range.