

SYNTHETIC SURFACE BOX TYPE 4056

80/31-200

For distribution valves, H-4056P HD-GG, Classic

Water Supply

AVK offers a wide range of fixed and height adjustable surface boxes in various dimensions, which can be used in many fields of application. Apart from economic benefits, AVK synthetic surface boxes are lightweight, user-friendly, easy to open, noiseless and maintenance free. Most of AVK surface boxes are designed and approved according to DIN/EN standards, but can also be designed according to local standards or customer specifications. The carbon footprint (CO₂ emission) of synthetic surface boxes, measured from resource to end of life, is significantly lower compared to surface boxes made of traditional materials, making AVK surface boxes ecologically sound.

Use:

Fixed height surface box with cast iron lid and square top, for distribution valves, standard lid inscription: W

Features:

- Lightweight, user-friendly, silent and maintenance free
- 100% recyclable and significantly less use of resources compared to traditional materials
- Manufactured out of high grade recycled materials
- Ribs in housing ensure optimal fixation in road foundation
- Selected materials for housing and lid ensure easy opening at all times
- Heat resistant to max. 250 °C
- Suitable for low-temperature applications
- Due to rectangular top ideal solution for pavement installation
- D400 load bearing capacity on complete surface*

Design/Test/Approval:

- Designed according to DIN 4056
- Tested according to DIN3580-2
- DVGW certificate DW-4530BN0470

Optional

- Various colours and lid inscriptions possible
- Available as lockable version making the surface box tamperproof

*Results of the load-bearing capacity test on the complete surface, following the internally used load application method, and declaring the load-bearing capacity according to the corresponding class as per EN 124-1:2015, clause 7.2, table 4

Accessories:

Support tile UST
Top frame gate valve




The designs, materials, dimensions and specifications shown are subject to change without notice due to the continuous development of our product range.

SYNTHETIC SURFACE BOX TYPE 4056

For distribution valves, H-4056P HD-GG, Classic

80/31-200



Component list:

1. Lid	Cast iron GJL-200 (GG-20)	3. Bolt, hexagon head	Stainless steel A2-70
2. Housing	PA+		

Metallic components may be substituted with equivalent or higher-grade materials without prior notice, provided that this is in compliance with the approvals.

Reference nos. and dimensions:

Reference no.	Do1 mm	DI mm	Dc1 mm	Di1 mm	Df mm	H3 mm	Weight Box / kg	Weight Lid / kg	Theoretical weight/kg
80-31-2000000	186	160	140 / 106	180	270	274	2.7	3.9	6.6
80-31-2000003	186	160	140 / 106	180	270	274	2.7	3.9	6.6